AMENDMENTS TO THE CLAIMS

Following is a complete set of claims as amended with this Response. This complete set of claims includes amended claims 1 and 18.

1. (Currently Amended) For use in an implantable medical device, a A biocompatible, biostable, corrosion-resistant wire strand comprising: for a cardioverting and/or defibrillating coil electrode of an implantable cardiac lead, the wire strand comprising:

a core comprising a plurality of electrically conductive, low electrical resistance filaments embedded in an electrically conductive matrix; and

a low electrical resistance, substantially chemically inactive cladding discrete from the matrix.

- 2. (Original) The wire strand of claim 1 in which: the core is substantially devoid of interstices.
- 3. (Original) The wire strand of claim 2 in which: the core comprises a drawn filled tube (DFT).
- 4. (Original) The wire strand of claim 2 in which: the core comprises a drawn brazed strand (DBS).
- (Original) The wire strand of claim 1 in which:
 the plurality of filaments comprise a material selected from the group consisting of silver, gold and a low electrical resistance conductive polymer.

6. (Original) The wire strand of claim 1 in which:

the matrix comprises a material selected from the group consisting of MP35N, tantalum, titanium and niobium.

7. (Original) The wire strand of claim 1 in which: the plurality of filaments comprise silver; and

the matrix comprises MP35N.

- 8. (Original) The wire strand of claim 7 in which: the core comprises a 1xN strand, where N = at least 2.
- 9. (Original) The wire strand of claim 8 in which: N = 19.
- (Original) The wire strand of claim 7 in which:
 the plurality of filaments comprise 10-35% by weight of the core.
- 11. (Original) The wire strand of claim 1 in which:

the cladding comprises a material selected from the group consisting of platinum, iridium, rhodium, palladium and alloys thereof, including a platinum/iridium alloy.

- 12. (Original) The wire strand of claim 1 in which: the filaments are braided.
- 13. (Previously Presented) An implantable cardiac lead for transmitting electrical signals between an implantable medical device and selected body tissue in the heart, the lead comprising:

a lead body having a proximal end and a distal end, the proximal end of the lead body carrying a connector assembly connectable to the implantable medical device; and

PATENT

at least one cardioverting and/or defibrillating coil electrode on the distal end of the lead body, the at least one cardioverting and/or defibrillating coil electrode being electrically connected to a terminal contact on the connector assembly, the at least one cardioverting and/or defibrillating coil electrode comprising a biocompatible, biostable, corrosion-resistant wire strand comprising (a) a core comprising a plurality of electrically conductive, low electrical resistance filaments embedded in an electrically conductive matrix and (b) a low electrical resistance, substantially chemically inactive cladding enclosing the core, the cladding being discrete from the matrix.

- 14. (Previously Cancelled)
- 15. (Previously Presented) The lead of claim 13 further comprising: at least one pacing and/or sensing electrode.
- (Previously Cancelled)
- 17. (Original) The lead of claim 13 in which: the core of the wire strand is substantially devoid of interstices.
- (Currently Amended) A wire strand comprising: for a cardioverting and/or defibrillating coil electrode of an implantable cardiac lead, the wire strand comprising:

a cladding layer comprising a material selected from the group consisting of platinum, a platinum/iridium alloy, iridium, rhodium and palladium; and

a drawn filled tube core comprising a plurality of filaments embedded in a matrix, each of the plurality of filaments comprising a material selected from the group consisting of silver, gold and a low electrical resistance conductive polymer, and the matrix comprising a material selected form the group consisting of MP35N, tantalum, titanium and niobium, the cladding layer being discrete from the matrix.

- 19. (Previously Presented) The lead of claim 13 in which: the filaments are braided.
- 20. (Previously Presented) The wire strand of claim 18 in which: the plurality of filaments are braided.